

PIPE NIPPLES

O.D.	1/8" -6"
Length	3/4" -24"; 19mm-500mm; Or as per customer's request
Thickness	SCH10 SCH20 SCH40 SCH80 SCH160; CLASS A, CLASS B, CLASS C
Surface	Hot Dipped Galvanized, Electro Galvanized, Natural finished, Chemical black
Threads	DIN, BS, NPT, Metric, BSPT, BSP, NPS (ISO7/1, DIN 2999, ANSI B1.20.1)
Dimension	BS EN10241, ASTM A733, DIN2982
Type	Close Nipple, Short Nipple, Shoulder nipple, Long Nipple, Running Nipple, Barrl Nipple etc
Usage	Convey Water, Oil, Gas, Steam and so on
Mechanical Properties	Tensile Strength $\geq 320\text{N/mm}^2$
	Yield Strength $\geq 195\text{N/mm}^2$
	Elongation $\geq 20\%$
Hydraulic Test	Working Pressure: Max 1.5MPa
	Test Pressure: Max 2.5MPa
Temperature:	-20 ~ 120 °c
Production Capacity	60000 MT per Year
Lead Time	Within 30 Days if enquiry not more than 10x20' Container
Factory Certificate	ISO, SGS, ITS, BSI, Famous Brand Enterprise in Hebei, China

